

MightyOne Re-Conditioning Process

MightyOne is a urethane finish, very hard, yet flexible, and extremely chemical resistant. Typical wear-life, one coat of MightyOne finish will last approximately 18 months. This is with average use, care, and maintenance.

Daily traffic on any floor, even with the most strict maintenance, will cause tiny micro-scratches in the finish. Over time, the micro-scratches will cause a slight loss of gloss and distortion to the finish.

Because of the toughness and resiliency of MightyOne, it is possible to revive the finish in between the application schedule. This sometimes is a nice temporary way to 'pop' the shine. However, this does not replace the application and protection of a fresh coat of MightyOne.

Because of the uniqueness of MightyOne, the heat caused from friction allows the surface to 'self-heal' the micro-scratches without removing or sacrificing the finish.

To Properly Re-condition the MightyOne:

1. *Vacuum or microfiber dry mop the floor, removing all dust and dirt particles. Repeat.*
2. *With a mixture of CLN-100 Daily Neutral Cleaner, clean the floor.*
Note: Proper cleaning is extremely important. If particles of sand are remaining on the surface, the sand will scratch the finish during the conditioning process.
3. *After washing, allow the floor to dry completely.*
4. *With a high-speed floor machine (250-500 rpm) equipped with a micro-fiber (broken fiber) bonnet pad or a hogs-hair pad go over the main traffic and slightly worn areas of the floor. As passes are made across the floor (holding the pad long enough on the surface to cause friction heat), there will be a visual change in the shine over the surface.*
5. *The floor is now ready for service*

Special Note: If in any areas of the floor, prior to or during the conditioning process there is a notice of bare surface (finish worn away), this is the point in time when an additional finish coat of MightyOne is needed. Follow Instructions in the Guide for MightyOne Re-application.

